



Shell
LubeMatch

MITSUBISHI

Shogun/Pajero/Montero Turbo Diesel 2.8
DT 1994-1999



Application		Recommendation	Capacity (ltr)
Engine (DT)	Premium	HELIX HX5 10W-40 (c)	6.5 / 7.8 (a)
	Standard	Helix HX5 15W-40	
Manual Transmission		Spirax S2 G 80W-90 (b)	3.7
Automatic Transmission	Premium	Spirax S2 ATF D2 (d)	8.5
	Standard	Spirax S2 ATF D2	
Differential	Premium	Spirax S3 AX 80W-90	3.2
	Standard	Spirax S2 A 80W-90	
Coolant (30%)		Refer to Technical 914430991103	8.0 - 10.5
Brake & Clutch Fluid	Premium	Brake and Clutch Fluid DOT 3	
	Standard	Brake and Clutch Fluid DOT 3	
Front Differential	Premium	Spirax S3 AX 80W-90	1.2
	Standard	Spirax S2 A 80W-90	
Power Steering	Premium	Spirax S2 ATF D2	
	Standard	Spirax S2 ATF D2	
Transfer Box	Premium	Spirax S2 G 80W-90	2.5 / 2.9
	Standard	Spirax S2 G 90	
Wheel Bearings		Gadus S3 V220C 2	

General Notes

Lubricant / Capacity Notes

- a. Without/With oil cooler
- b. Alternative recommendations: 75W-85W; 75W-90
- c. Alternative recommendations, Engine (Diesel): <10°C, 5W-30; -20°C to 40°C, 10W-30; >-15°C, 15W-40; >-10°C, 20W-40; 0°C to 40°C, 30
- d. Alternative recommendations, >1996: Refer To Technical 914430991103

Engine

Months Max 6

Km Max 7500