



ROYAL ENFIELD

SPECIFICATIONS

Engine

Type Parallel twin, 4 stroke, SOHC, Air-Oil Cooled Displacement 648cc Bore x stroke 78 mm x 67.8 mm **Compression Ratio** 9.5:1 **Maximum Power** 34.6 kW (47PS) @7250 rpm **Maximum Torque** 52.3 Nm @5650 rpm Clutch Wet, multi-plate 6 Speed constant mesh Gearbox **Electronic Fuel Injection Fuel Supply** Air Cleaner Paper element **Engine Start** Electric 99 g/km **CO2** Emissions

76.3 dB(A)

FPL 1.55 W LED

2.5 W, LED

Steel Tubular Spine Frame

USB 2.0 Type A - 5V 2A Output

Chassis & Suspension

Type Front suspension Rear suspension

Noise Emissions

Electricals

Battery Head Lamp Tail Lamp Charging Port 43mm Upside Down Telescopic Fork, 120mm travel Twin Shocks, 101mm travel, preload adjustable 12 volt, 12 Ah, VRLA Dimensions

Wheelbase Ground Clearance Length Width Height Seat Height Kerb Weight Fuel Capacity

Brakes & Tyres

Tyres Fr. Tyres Rr. Brakes Front Brakes Rear ABS 1500 mm 135 mm 2260 mm 890 mm (without mirrors) 1155 mm 740 mm 241 kg (with 90% fuel & oil) 15.7 litres

100/90 - 19 M/C 57H (Tubeless Type) 150/80 B16 M/C 71H (Tubeless Type) Single 320mm disc, twin piston floating caliper Single 300mm disc, twin piston floating caliper Dual Channel