



HERO HONDA MOTORS LTD., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110 057.
Phone No.: 011-46044100, 011-26142451, 011-26144121. Fax: 2614 3198, 2614 2312 Website: www.hunkbike.com

Accessories & features shown may not be a part of the standard fitment. It is our endeavour to constantly improve our products.
This could lead to changes in product specifications without notice. Hero Honda Hunk complies with BS III norms. *Warranty for a period of 3 years or 40,000 kms from the date of purchase, which ever is earlier.



Hunk

NO ONE MESSES WITH IT.





RAGING BULL INSIGNIA



RED HOT LED TAIL LIGHT



ANO-DIGITAL SPEED PANEL
Analog meets digital in this chrome ringed flame orange console



CONTOURED VISOR
The visor gets the muscle edge



FLARED FENDERS
AND TUBELESS TYRES



RIDGED MUFFLER COVER WITH
FRONT AND REAR DISC BRAKES



This revolutionary technology moves the air and petrol mixture within the combustion chamber in a whirling motion in order to improve combustion. This provides for the best balance of power and fuel efficiency. Hence, more mileage and less pollution.



Panther Black



Ebony Grey



Force Silver



Bold Brown



Marine Green



Sports Red



Blazing Red

ENGINE

TYPE Air cooled, 4-Stroke Single Cylinder OHC
DISPLACEMENT 149.2CC
MAXIMUM POWER 10.6 KW (14.4PS) @ 8500 rpm
MAXIMUM TORQUE 12.80 N-m @ 6500 rpm
ACCELERATION 0-60 Km/h in 5 seconds
STARTING Self Start
IGNITION AMI - Advanced Microprocessor Ignition System

TRANSMISSION

CLUTCH Multiplate Wet
GEAR BOX 5 Speed Constant Mesh
CHASSIS TYPE Tubular, Diamond Type

SUSPENSION

FRONT Telescopic Hydraulic Shock Absorbers
REAR Swing Arm with Nitrox GRS (Gas Reservoir Suspension)

BRAKES

FRONT Disc - 240 mm
REAR Disc - 220 mm
Drum - 130 mm Internal expanding shoe type (Optional)

WHEEL AND TYRES

RIM SIZE Front - 18" x 1.85" Alloy Wheel
Rear - 18" x 2.15" Alloy Wheel

TYRE SIZE Front - 2.75" x 18" - 42 P, Tubeless Tyres
Rear - 100/90 mm x 18" - 56P, Tubeless Tyres

TANK

FUEL CAPACITY 12.4 Ltrs (Min)
FUEL RESERVE 2.2 Ltrs (Usable Reserve)

WEIGHT

KERB WEIGHT 146 Kg

ELECTRICALS

BATTERY 12 V - 4 Ah , MF Battery
HEAD LAMP 12V - 35W / 35W - Halogen Bulb (Multi-Reflector Type)
TAIL LAMP 12V - 0.5W / 4.1 W LED Lamp
INDICATORS 12V- 10W (Amber Bulb) x 4 nos (Multi- Reflector - Clear Lens)

DIMENSIONS

LENGTH 2080 mm
WIDTH 765 mm
HEIGHT 1095 mm
WHEELBASE 1325 mm
SADDLE HEIGHT 795 mm
GROUND CLEARANCE 145 mm

OPTIMUM POWER AND MILEAGE

NEW GENERATION LOW FRICTION TECHNOLOGY CORE 2 ENGINE Delivers optimum power, torque and acceleration along with better fuel efficiency.

ADVANCED MICROPROCESSOR IGNITION SYSTEM (AMI) WITH CARBURETTOR CONTROLLED VARIABLE IGNITION (CCVI) A digitally mapped Capacitor Discharge Ignition (CDI) varies ignition timing based on engine speed and throttle position. Offers a crisp throttle response, superior drivability and the real thrill & joy of biking.

LOW MAINTENANCE

NEW GENERATION ENGINE OIL A new generation 10w30 SJ, JASO MA Grade Oil flows through the heart of this beast. It ensures longer oil change intervals of 6000 kms and improves engine performance.

SUPERIOR COMFORT

GAS RESERVOIR SUSPENSION (GRS) The ultimate support for the rippling muscles; this nitrox based suspension system ensures the smoothest ride.

TUBELESS TYRES Tubeless Tyres make every terrain a hiccup free ride.

MUSCULAR STYLING

FUEL TANK Broad, muscular fuel tank with brawny shoulders.

HEADLIGHT & VISOR Glaring headlight and aggressively styled visor.

SADDLE A contoured sporty saddle with a stepped pillion seat.

REAR COWLS Muscular rear cowls.

WHEEL & BRAKE 5 spoke black alloy wheels with 240 mm front and 220 mm rear disc brakes. 130 mm rear drum brakes optional.

INDICATORS Bright clear lens indicators.